AEROSOL AEROSOL AEROSOL AEROSOL AEROSOL AEROSOL AEROSOL

Environmental Sanitation Chemicals Since 1964

North Woods®

Superior CHEMICAL CORPORATION

Environmental Health & Sanitation Chemicals

Technical Data

DRY LUBE

DRY PTFE LUBRICANT & RELEASE AGENT

DESCRIPTION

DRY LUBE lubricant & release agent is a chemically inert, non-oily, fast drying formulation made with extremely fine polytetrafluoroethylene powder. This outstanding formulation features microscopic film forming properties and resists temperatures from -100˚F to +500˚F. DRY LUBE leaves an odorless, stainless coating that is more slippery than silicone, graphite or oil. Reduces low speed friction. The DRY LUBE film is not affected by most chemicals and when used as a release agent, allows parts to be painted without cleaning.

PRECAUTIONS

Keep Out Of Childrens Reach

USES/BENEFITS

- Oil Free and Odorless
- Greaseless
- Non-staining and Fast Drying
- Heat Stable from -100˚F to 500˚F
- Contains No Chlorinated Solvents

FOR USE ON:
- Plastic
- Metal
- Aluminum
- Wood
- Rubber
- Glass

FOR USE BY:
- Bottling Plants
- Dairies
- Processing & Packaging Plants
- Manufacturing Plants
- Maintenance Departments
- Assembly Operations

DIRECTIONS FOR USE

Shake can vigorously, rattling agitator ball for a minimum of 1 full minute. Surface to be treated must be clean and dry. Hold container 5 to 10 inches from surface and spray a thin film over area.

SPECIFICATIONS

Color	White
Specific Gravity	0.766
Net Weight	10 ounces

EXCELLENCE SINCE 1964